



## HEMPEL'S GELCOAT CLEANING GEL 69017

<b>Description:</b>	HEMPEL'S GELCOAT CLEANING GEL 69017 is a strong, high efficient, non-abrasive cleaning gel.
<b>Recommended use:</b>	For removal of stubborn stains such as rust and exhaust staining, waterline deposits and fender marks on gelcoat and painted surfaces over small/local areas. The chemical process eliminates the need of scraping the surface. Due to the gell formulation HEMPEL'S GELCOAT CLEANING GEL 69017 can be used on vertical surfaces.
<b>Availability:</b>	Part of European Yacht assortment. Local availability subject to confirmation.
<b>PHYSICAL CONSTANTS:</b>	
Shade nos/Colours:	99980/ Blue.
Flash point:	None.
Specific gravity:	1 kg/litre [8.6 lbs/US gallon]
pH:	1.2
VOC content:	1 g/l [0 lbs/US gallon] <i>The physical constants stated are nominal data according to the HEMPEL Group's approved formulas.</i>
<b>APPLICATION DETAILS:</b>	
<b>Safety:</b>	Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult HEMPEL Safety Data Sheets and follow all local or national safety regulations.
<b>SURFACE PREPARATION:</b>	Wash the area to be treated with HEMPEL'S PRE-CLEAN 67602 as instructed and rinse with fresh water. Allow the surface to dry
<b>APPLICATION CONDITIONS:</b>	Shake well before use. Apply the product with a brush onto the stained area. Leave for 15-30 minutes and remove with high pressure, fresh water hosing, agitating with a brush if required.
<b>SUBSEQUENT COAT:</b>	If high gloss is desired, apply:HEMPEL'S CUSTOM MARINE POLISH 67444. Finish with:HEMPEL'S WAX 69033 orHEMPEL'S WAX TecCell 69034.
<b>REMARKS:</b>	The surface temperature should be above: 5°C/41°F Do not apply in direct sunlight.
<b>Application(s)</b>	The product contains acidic components. Stainless steel parts should be protected against contact with the product as discolouration could occur.
<b>Storage Conditions:</b>	Store at temperatures: Minimum: 10°C/50°F
<b>Note:</b>	<b>HEMPEL'S GELCOAT CLEANING GEL 69017</b> 6901799980 <b>The information given in the Product Data Sheet is intended for commercial use.</b>
<b>ISSUED BY:</b>	HEMPEL A/S

This Product Data Sheet supersedes those previously issued.

For explanations, definitions and scope, see "Explanatory Notes" available on [www.hempel.com](http://www.hempel.com). Data, specifications, directions and recommendations given in this data sheet represent only test results or experience obtained under controlled or specially defined circumstances. Their accuracy, completeness or appropriateness under the actual conditions of any intended use of the Products herein must be determined exclusively by the Buyer and/or User.

The Products are supplied and all technical assistance is given subject to HEMPEL's GENERAL CONDITIONS OF SALES, DELIVERY AND SERVICE, unless otherwise expressly agreed in writing. The Manufacturer and Seller disclaim, and Buyer and/or User waive all claims involving, any liability, including but not limited to negligence, except as expressed in said GENERAL CONDITIONS for all results, injury or direct or consequential losses or damages arising from the use of the Products as recommended above, on the overleaf or otherwise. Product data are subject to change without notice and become void five years from the date of issue.