



HEMPEL'S THINNER 08451

Description:

HEMPEL PAINT is produced and supplied in such a way that thinning is normally not necessary provided the paint is properly mixed/stirred.
However, if the paint is to be applied in a low film thickness (for instance as a "sealer coat") or if the paint has become too thick, e.g. in cold weather, the HEMPEL THINNER(s) indicated on the product data sheet may be added to obtain a consistency most suitable for application. As a general rule, thinning should be kept at a minimum as the quality of the paint work will suffer from too liberal thinning. However, if application is to take place at high temperatures (air and/or steel), thinning may even beyond the limits mentioned on the data sheets exceptionally be necessary in order to avoid dry-spray and poor film formation.
HEMPEL'S THINNERS are blended to give the best results with regard to brush ability, spray properties, etc.
In some cases ordinary solvents may substitute. As such products are beyond our control, we disclaim any responsibility for the results.
In each case the respective product data sheet and - when available - the APPLICATION INSTRUCTIONS should be consulted. As regards the use of THINNERS for cleaning of tools, see REMARKS overleaf.

Recommended use:

HEMPEL'S LIGHT PRIMER 45551.
Cleaning of tools:HEMPEL'S HIGH PROTECT 35651, HEMPEL'S EPOXY ADHESIVE 05674, HEMPEL'S SEALER 599, HEMPEL'S EPOXY FILLER 35251/3

Availability:

Part of European Yacht assortment. Local availability subject to confirmation.

PHYSICAL CONSTANTS:

Shade nos/Colours: 00000/ Colourless.
Flash point: 26 °C [78.8 °F]
Specific gravity: 0.9 kg/litre [7.1 lbs/US gallon]
VOC content: 851 g/l [7.1 lbs/US gallon]

The physical constants stated are nominal data according to the HEMPEL Group's approved formulas.

APPLICATION DETAILS:**Safety:**

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult HEMPEL Safety Data Sheets and follow all local or national safety regulations.

REMARKS:

Cleaning of tools:

Tools can usually be cleaned with the THINNER prescribed for the product.

Note: **HEMPEL'S THINNER 08451** 0845100000

The information given in the Product Data Sheet is intended for commercial use.
HEMPEL A/S

ISSUED BY:

This Product Data Sheet supersedes those previously issued.

For explanations, definitions and scope, see "Explanatory Notes" available on www.hempel.com. Data, specifications, directions and recommendations given in this data sheet represent only test results or experience obtained under controlled or specially defined circumstances. Their accuracy, completeness or appropriateness under the actual conditions of any intended use of the Products herein must be determined exclusively by the Buyer and/or User.

The Products are supplied and all technical assistance is given subject to HEMPEL's GENERAL CONDITIONS OF SALES, DELIVERY AND SERVICE, unless otherwise expressly agreed in writing. The Manufacturer and Seller disclaim, and Buyer and/or User waive all claims involving, any liability, including but not limited to negligence, except as expressed in said GENERAL CONDITIONS for all results, injury or direct or consequential losses or damages arising from the use of the Products as recommended above, on the overleaf or otherwise. Product data are subject to change without notice and become void five years from the date of issue.